

E50

Compact Electric Elevator

CAMBRIDGE
ELEVATING

Cab Finishes



MDF (UNFINISHED)
—
(STANDARD)



WALNUT
—
MELAMINES (STANDARD)



MAPLE
—
MELAMINES (STANDARD)



GIBRALTAR
—
MELAMINES (STANDARD)




PALOMINO
—
MELAMINES (STANDARD)



KODIAK
—
MELAMINES (STANDARD)



ALABASTER
—
MELAMINES (STANDARD)



WHITE
—
MELAMINES (STANDARD)



Elevator Fixtures

Call Station



Lighting




Car Operating Panel (COP)



Fixture Finish



Cab Entrance



E50

Compact Electric Elevator

CAMBRIDGE
ELEVATING



SPECIFICATIONS

Weight Capacity: 500lb (227kg)

Rated Speed: 35 ft/min (0.18m/s) nominal

Max Travel: 35ft (10.7m)

Max # of Stops: 4

Required Minimum Pit Depth: 6 in (152.4mm)

Minimum Overhead Clearance: 96 in (2438.4mm)

Power Source: 220 VAC, 60 Hz, 30 Amp & 120 VAC, 60 HZ, 15 Amp single phase power

Lighting Disconnect Supply: 110 VAC

Drive System: Counterweight chain drive

Noise Level: 66-69 dBA

Hoistway Size: 50 in x 50 in (1270mm x 1270mm)

Cab Finish: Choice of melamine cab walls with white melamine ceiling OR Medium Density Fiberboard (MDF) walls & ceiling, finished by others

Cab Floor: By others with 1/2 in (12.7mm) recess

STANDARD FEATURES

Two recessed LED cab lights

Automatic opening bi-fold cab door with white panels

Dual illuminated push buttons on hall calls and Car Operating Panel (COP)

Emergency stop switch on COP

Digital Position Indicator (DPI) with animated direction arrows on COP

Emergency battery lowering

Touch-tone telephone in cab

Overspeed governor